

GENERATING SET

GE 7500 HSX

FEATURES

- Engine shut down for low level oil
- Electric starter
- Sockets: 1x400V 16A 3P+N+T CEE - 1x230V 16A 2P+T CEE
- ELCB-GFI (Ground Fault Interruptor)
- Circuit breaker
- Super Silenced
- Ready for connection to automatic transfer unit EAS
- Meets EC Directives for safety and noise level



The images are for reference

Standard Equipment	 Petrol engine	 Air cooling	 Electric Starter	 Battery 12V	 Engine shut down (oil)	 Hours-meter	 Low fuel indicator				
	 Synchronous alternator	 Compound	 Sockets	 Sockets	 ELCB-GFI	 Circuit breaker	 Voltmeter	 Ready for EAS/TCM	 Local/Remote Start selector		
Options on request	• Automatic transfer unit (AMF) EAS 15-806 • Remote control TCM15 • Earthing kit • Exhaust extension • Moving wheels CTM7										
Versions on request	• Schuko sockets										

Technical data

GE 7500 HSX

A.C. GENERATION - 50 Hz - Three-phase synchronous alternator, self-excited, self-regulated

*Stand-by three-phase power	7.5 kVA (6 kW) / 400 V / 10.8 A
*PRP three-phase power	6.5 kVA (5.2 kW) / 400 V / 9.4 A
*PRP single-phase power	4 kVA / 230 V / 17.4 A
Cos φ	0.8
Insulation class	H

* Output powers according to ISO 8528-1

ENGINE - 4-stroke petrol, OHV, Air cooling

Model	Honda GX 390
* Stand-By net power	8.2 kW (11.1 HP)
* PRP net power	6.4 kW (8.7 HP)
Cylinders/ Displacement	1/ 389 cm ³
Speed	3000 rpm
Fuel consumption (75% of PRP)	2.4 l/h

* Powers according to SAE J1349

GENERAL SPECIFICATIONS

Tank capacity	20 l
Running time (75% of PRP)	8.3 h
IP protection degree	IP 23
* Dimensions LxIxxh	1060x570x665 mm
* Dry weight	165 kg
** Measured acoustic power LwA (pressure LpA)	88 dB(A) (63 dB(A) @ 7m)
** Guaranteed acoustic power LwA (pressure LpA)	89 dB(A) (64 dB(A) @ 7m)

* Dimensions and weight without trolley/trailer / **Acoustic power according to European Directive 2000/14/EC