

GENERATING SET GE SX-7554 YDT

The images are for reference



FEATURES

- Bunded base suitable to contain any liquids leakage from engine avoiding environmental pollution
- The rounded edges of the canopy designed for rainwater drainage away
- Engine cowling side, can be completely opened, which facilitates all maintenance operations
- Central lifting eye
- Digital engine and generator control module
- Isometer
- Emergency stop button
- Supersilenced
- Automatic voltage regulator
- Compliant with DGUV -I 203-032 regulation
- Meets EC directives for noise and safety



air cooled



diesel



three-phase



electric start

POWER RATINGS	
* Stand-By three-phase power (LTP)	7 kVA (5.6kW) /400V/ 10.1A
* PRP three-phase power	6 kVA (4.8 kW) /400V/ 8.7A
* PRP single-phase power	4.8 kVA/kW /230V/ 20.9A
* COP single-phase power	/
Frequency	50 Hz
Cos φ	0.8

* Powers declared according to ISO 8528

DEFINITION

Valid declared powers up to the followings environmental conditions: temperature 25°C, altitude 100 meters above sea level)

LTP power: stand-by power: Maximum available power for use with variable loads for a yearly number of hours limited at 500 h. No overload is admitted.

PRP power: continue power with variable loads. Maximum power for use with variable loads for a yearly illimited nubers of hours.

COP power: continuous power with constant load. Maximum power for use with constant loads for a yearly unlimited numbers of hours.

ENGINE 3000 RPM

4 STROKE, NATURAL ASPIRATED	
Model	YANMAR L 100 V
Stand-By net power	6.3 kWm (8.5 hp)
PRP net power	5.7 kWm (7.7 hp)
COP net power	/
Cylinders / Displacement	1 / 435 cm ³ (0,435 lt.)
Bore / Stroke	86 / 75 (mm)
Compression ratio	20 : 1
BMEP (Brake Mean Effective Pressure : LTP - PRP)	/
Speed governor type	Mechanical
FUEL CONSUMPTION	
110 % (Stand-by power)	1.9 lt./h
100 % to PRP	1.7 lt./h
75 % to PRP	1.2 lt./h
50 % to PRP	0.8 lt./h
COOLING SYSTEM	
Total system cap. - only engine	/
Fan air flow	/
LUBRICATION SYSTEM	
Total oil system capacity	/
Oil capacity in sump	1.6 lt.
Oil consumption at full load	/

EXHAUST SYSTEM	
Maximum exhaust gas flow	/
Max. exhaust gas temp.	/
Maximum back pressure	4.3 kPa (0.043 bar 440 mmH ² O)
External diameter exhaust pipe	/
ELECTRICAL SYSTEM	
Starter motor power	0.8 kW
Battery charging alternator cap.	15 A
Cold start	- 10°C
With cold start aid	/
AIR FILTER	
Combustion air flow	/
HEAT REJECTED AT FULL LOAD	
To exhaust system	/
To water and oil	/
Radiated to room	/
To charge cooler	/



ALTERNATOR

SYNCHRONOUS, THREE-PHASE, SELF-EXCITED, SELF-REGULATED	
Continuous power	9 kVA
Stand-by power	10 kVA
Three phase voltage	380 ÷ 415 Vac
Frequency	50 Hz
Cos φ	0.8
Model A.V.R.	Analogic
Voltage regulation acc.	± 1 %
Sustained short circuit current	3 In
Transient dip (100% load)	< 25 %
Recovery time	< 0.5 sec.
Efficiency at 100% load	/
Insulation	Class F/H
Connection - Terminals	Star - N°4
Electromagnetic compatibility (R.F.I. suppr.)	/
Waveform distorsion - THD	< 5 %
Telephone interference - THF	/

REACTANCES (9 KVA - 400V)	
Direct axis synchronuos - Xd	/
Direct axis transient - X'd	/
Subdirect axis transient - X''d	/
Quadrature axis synchronuos - Xq	/
Quadr. axis subtransient - X''q	/
Negative sequence - X2	/
Zero sequence - X0	/
TIME CONSTANTS	
Transient - T'd	/
Subtransient - T''d	/
Open circuit - T'do	/
Armature - Ta	/
Short-circuit ratio Kcc	/
IP protection degree	IP 54
Cooling air flow	/
Coupling Bearing	Direct J609b - N°1

GENERAL SPECIFICATIONS

Fuel tank capacity	23 lt.
Running time (75% to PRP)	19 h
Starter battery	12 Vdc -37Ah / 330A CCA(EN)
IP protection degree	IP 44

* Measured acoustic power LwA (pressure LpA)	91.6 dB(A) (66.6 dB(A) @ 7m)
* Guaranteed acoustic power LwA (pressure LpA)	93 dB(A) (68 dB(A) @ 7m)
Performance class	G2

* Acoustic power in accordance with Directive 2000/14/EC



AUTOMATIC CONTROL PANEL

- Controller InteliNano Plus
- Controller supply switch
- Battery charge warning light fault
- Emergency stop button
- TCM 35 remote control plug
- Isometre
- Circuit breaker
- ELCB-GFI (Ground Fault Interruptor) for 230V 16A sockets
- Output sockets : 1x400V 16A 3P+N+T IP67
2x230V 16A 2P+T Schuko IP68
- Earth terminal (PE)

INTELINANO PLUS CONTROLLER CHARACTERISTICS	
Operating mode	<ul style="list-style-type: none"> • MAN.- AUTO
Display	<ul style="list-style-type: none"> • Graphic back-light LCD display 128x64 pixels
LEDs	<ul style="list-style-type: none"> • Engine operation • AUTO operating mode • Alarm
Buttons	<ul style="list-style-type: none"> • START button • STOP button • AUTO button • N° 2 buttons for controller programming
Generator Measures	<ul style="list-style-type: none"> • Voltage : L1-L2 • Current : I1 • Powers : kVA • Frequency
Engine Measures	<ul style="list-style-type: none"> • Water temperature (optional) • Oil pressure (optional) • Fuel level • Rpm meter • Battery voltage • Maintenance • Hours meter

Generator Protections	<ul style="list-style-type: none"> • Short circuit • Over-Undervoltage • Over-Underfrequency • Phase sequence
Engine Protections	<ul style="list-style-type: none"> • Overspeed • High water temperature warning • Low oil pressure warning • Low fuel level warning • Under battery voltage • Battery charge alternator failure • Start failure • Stop failure • Emergency stop
AMF functions (Automatic control panel only)	<ul style="list-style-type: none"> • Measure mains voltage : L1-L2 / L2-L3 / L3-L1 - N-L1 / N-L2 / N-L3 • Measure mains frequency • Three phase detection • Over-Under mains voltage • Over-Under mains frequency • Phase sequence
Features	<ul style="list-style-type: none"> • Event log and alarms (10 events) • Operator interface with icons, no text • Remote Start and Stop • Pre-heating • Fully programmable from the panel or from PC • Direct connection to engines with ECU via Can bus J1939 • Manual operation (MRS) with remote start • IP65 protection • Operation temperature: -20°C / +70°C
Communication	<ul style="list-style-type: none"> • Setup USB port • CAN BUS interface (J1939 only)



WEIGHT - DIMENSIONS AND ACCESSORIES

GE SX-6500 YDT




DRY WEIGHT MACHINE:
• 221 Kg

Generating set pictured may include optional accessories.



DIMENSIONS DRAW (mm)



⊕ OPTIONS ON REQUEST

- Remote control TCM35
- Earthing kit
- Trolley CTM2
- Road trailer CTV4
- Exhaust extension

☀ VERSIONS ON REQUEST

• /

📄 FACTORY INSTALLATION OPTIONS

• /

GENERAL INFORMATION

COMPLIANCE GENERATING SETS WITH EC DIRECTIVES AND STANDARDS

- 2006/42 / EC (Machines Directive)
- 2014/35 / EU (Low Voltage Directive)
- 2014/30 / EU (EMC Directive)
- 2000/14 / EC (Directive Acoustic Emission for machines for use outdoors)
- ISO 8528 (Reciprocating internal combustion engine driven alternating current generating sets)



ISO 9001:2015 - Cert. 0192

WARRANTY

All devices are covered by the manufacturer's warranty.

The company reserves the right to change this specification without notice. For further information please contact the sales department.

© MOSA - Viale Europa, 59 - 20090 Cusago (Milano) - Italy - phone +39-0290352.1 - fax + 39-0290390466 E-mail: info@mosa.it Web site: www.mosa.it

